


| | |
|---|---|
| **Symbol:** | AX-200 |
| **Product groups:** | Meters and Clamp Probes |

# Product specifications

| | |
|---|---|
| **Type of meter:** | multifunction |
| **Kind of meter:** | AC pincers type, digital |
| **Measuring instrument features:** | automatic power-off, autoranging, HOLD function, low battery indicator, overflow indicator |
| **Kind of display used:** | LCD |
| **Display parameters:** | 3,5 digit (1999) |
| **Max. diameter of measured cable:** | 21mm |
| **AC current measuring range:** | 2A, 20A, 200A |
| **AC current measuring accuracy:** | ±(2.5% + 3 digit) |

| | |
|---|---|
| **DC voltage measuring range:** | 200mV, 2V, 20V, 200V, 600V |
| **DC voltage measuring accuracy:** | ±(0.8% + 3 digit) |
| **AC voltage measuring range:** | 2V, 20V, 200V, 600V |
| **AC voltage measuring accuracy:** | ±(1% + 3 digit) |
| **Resistance measuring range:** | 200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ |
| **Diode test:** | 1mA @1.5V |
| **Continuity test:** | acoustic indication, <70Ω |
| **Dimensions:** | 130x52x24mm |
| **Weight with battery:** | 135g |
| **Power supply:** | battery R03 AAA 1,5V x3 |
| **Measurement:** | AC current, AC voltage, DC voltage, resistance |
| **Conform to the norm:** | CAT III 600V, EN 61010 |
| **Protection:** | anti-overload OPP |
| **Standard equipment:** | test leads |
| **Battery/ rechargeable battery:** | battery R03 AAA 1,5V x3 |
| **Resistance measuring accuracy:** | ±(1%+2 digit) |

# Additional information

| | |
|---|---|
| **Gross weight:** | 0.226 kg |