


| | |
|---|---|
| **Symbol:** | AX-C715N |
| **Product groups:** | Laboratory instruments |

# Product specifications

| | |
|---|---|
| **Type of meter:** | calibrator |
| **Kind of calibrator:** | loop |
| **Kind of display used:** | LCD |
| **Display parameters:** | 4 digit |
| **DC voltage measuring range:** | 0...50V |
| **DC voltage measuring accuracy:** | ±(0.1% + 40mV) |
| **AC voltage measuring range:** | 0...500V |
| **DC current measuring range:** | 0...50mA |

| | |
|---|---|
| **DC current measuring accuracy:** | ±(0.1% + 40µA) |
| **Resistance measuring range:** | 5kΩ |
| **Test:** | diodes |
| **Continuity test:** | acoustic indication |
| **Operating temperature:** | 0...40°C |
| **Dimensions:** | 185x90x54mm |
| **Power supply:** | battery LR6 AA 1,5V x3 |
| **Measuring instrument features:** | 24V loop supply voltage, alarms breach of limit values, automatic power-off, low battery indicator, white LED torch |
| **Measurement:** | AC voltage, DC current, DC voltage, resistance |
| **Conform to the norm:** | CAT IV 600V |
| **Current measuring resolution:** | 10µA |
| **Voltage measuring resolution:** | 10mV DC |

# Additional information

| | |
|---|---|
| **Gross weight:** | 0.65 kg |