

Symbol:	AX-5002
Product groups:	Meters of environmental conditions

Product specifications

Type of meter:	temperature
Kind of meter:	digital
Kind of display used:	LCD
Display parameters:	4 digit
Temperature measuring range measured by probe:	-200...1300°C
Temperature measuring accuracy (measurement with probe):	±(0.1% + 0.7°C)

Non-contact temperature measuring range:	-50...300°C
Non-contact temperature measuring accuracy:	±(1.5% + 3°C)
Temperature measurement resolution:	0.1°C
Optical resolution:	2:1
Emissivity value:	0,95 (fixed)
Dimensions:	121x60x30mm
Power supply:	battery GR03 AAA 1,5V x3
Measuring instrument features:	automatic power-off, contact or non-contact temperature measurement, HOLD function, laser sight, low battery indicator, MIN/MAX/MEDIUM function
Standard equipment:	case, drop-like K-type probe, hand strap
Measurement:	non-contact temeprature (IR)
Measuring unit:	°C, °F
Related items:	5790D, 5793D, 5794D, 5795D, 5797D, BKP60, EX871515, EX881602, EX881603, EX881605, PKT-PTA, PKT-PTF-10, PKT-PTF-20, PKT-PTF-25, PKT-PTF-30, PKT-PTF-40, PKT-PTF-50, PKT-PTF-55, PKT-PTF-56, PKT-PTF-60, SE027, SE028, SE029, SE030, SE031, SE059, SE060, SE061, SE062, SE001, SE002, SE003, SE004, SE000, TESTO-06020393, TESTO-06020645, TESTO-06024592, TESTO-06024892, TESTO-06280020, TESTO-06281292, TESTO-06287533, TP200, TP400, TP870, TP873, TP873-5M, TP882, TP-111, TP-112, TP-02, TP-03, TP-04, TP-06, TP-08, TP-09, TPK-59, TPK-62, UTT10K, UTT12

Battery/ rechargeable battery:	battery GR03 AAA 1,5V x3
Illumination:	yes

Additional information

Gross weight:	0.436 kg