


| | |
|---|---|
| **Symbol:** | AX-3005DBL-3 |
| **Product groups:** | Laboratory Power Supplies |

# Product specifications

| | |
|---|---|
| **Type of laboratory power supply:** | standard |
| **Kind of power supply:** | linear, multi-channel |
| **Kind of display used:** | LCD x2 |
| **Display parameters:** | 3,5 digit |
| **Number of channels:** | 3 |
| **Output voltage:** | 0...30V DC |
| **Output current:** | 0...5A |
| **Output voltage 2:** | 0...30V DC |
| **Output current 2:** | 0...5A |

| | |
|---|---|
| **Output voltage 3:** | 5V DC |
| **Output current 3:** | 3A |
| **Supply voltage:** | 230V AC |
| **Voltage stabilisation:** | ≤0.02%+ 2mV |
| **Current stabilisation:** | ≤0.02%+ 2mA |
| **Dimensions:** | 270x310x180mm |
| **Measuring instrument features:** | simultaneous voltage and current readout, voltage and current stepless adjustment |
| **Standard equipment:** | mains cable, test leads |
| **Voltage (regulated) ripple and noise:** | ≤0.5mVrms |
| **Connectors for the country:** | Europe |

# Additional information

| | |
|---|---|
| **Gross weight:** | 13.35 kg |