


| | |
|---|---|
| **Symbol:** | AX-3005L-3 |
| **Product groups:** | Laboratory Power Supplies |

# Product specifications

| | |
|---|---|
| **Type of laboratory power supply:** | standard |
| **Kind of power supply:** | linear, multi-channel |
| **Kind of display used:** | LED x4 |
| **Display parameters:** | 3,5 digit |
| **Number of channels:** | 3 |
| **Output voltage:** | 0...30V DC |
| **Output current:** | 0...5A |
| **Output voltage 2:** | 0...30V DC |
| **Output current 2:** | 0...5A |

| | |
|---|---|
| **Output voltage 3:** | 5V DC |
| **Output current 3:** | 3A |
| **Supply voltage:** | 230V AC |
| **Output voltage resolution:** | 0.1V |
| **Output current resolution:** | 10mA |
| **Dimensions:** | 260x160x360mm |
| **Measuring instrument features:** | 2 regulated blocks that can operate in constant current or constant voltage modes and as serial, parallel or independent PSUs, programmable current limiter, simultaneous voltage and current readout, smart cooling control, very quiet fan operation, voltage and current stepless adjustment |
| **Protection:** | anti-overload OPP, short circuit protection SCP |
| **Voltage (regulated) ripple and noise:** | ≤1mVrms |
| **Connectors for the country:** | Europe |

# Additional information

| | |
|---|---|
| **Gross weight:** | 9.85 kg |