


| | |
|---|---|
| **Symbol:** | AX-2040 |
| **Product groups:** | Meters and Clamp Probes |

# Product specifications

| | |
|---|---|
| **Type of meter:** | multifunction |
| **Kind of meter:** | AC pincers type, digital |
| **Measuring instrument features:** | automatic selection of measurand, autoranging, contactless voltage detector, HOLD function, low battery indicator, overflow indicator |
| **Kind of display used:** | LCD |
| **Display parameters:** | (4000) |
| **AC current measuring range:** | 40...400A |
| **AC current measuring accuracy:** | ±(1.8% + 5 digit) |

| | |
|---|---|
| **DC voltage measuring range:** | 4...400V |
| **DC voltage measuring accuracy:** | ±(0.7% + 4 digit) |
| **AC voltage measuring range:** | 4...600V |
| **AC voltage measuring accuracy:** | ±(1.2% + 4 digit) |
| **Resistance measuring range:** | 0.4kΩ, 4MΩ, 40MΩ |
| **Pollution degree:** | 2 |
| **Power supply:** | battery LR6 AA 1,5V x2 |
| **Measurement:** | AC current, AC voltage, DC voltage, resistance |
| **Conform to the norm:** | CAT III 600V, EN 61010 |
| **Standard equipment:** | case, test leads |
| **Battery/ rechargeable battery:** | none |
| **Measurement memory:** | 10 |
| **Illumination:** | yes |
| **Resistance measuring accuracy:** | ±(0.8%+2 digit) |

# Additional information

| | |
|---|---|
| **Gross weight:** | 0.459 kg |