

Symbol:	AX-200
Product groups:	Meters and Clamp Probes

Product specifications

Type of meter:	multifunction
Kind of meter:	AC pincers type, digital
Measuring instrument features:	automatic power-off, autoranging, HOLD function, low battery indicator, overflow indicator
Kind of display used:	LCD
Display parameters:	3,5 digit (1999)
Max. diameter of measured cable:	21mm
AC current measuring range:	2A, 20A, 200A
AC current measuring accuracy:	±(2.5% + 3 digit)

DC voltage measuring range:	200mV, 2V, 20V, 200V, 600V
DC voltage measuring accuracy:	±(0.8% + 3 digit)
AC voltage measuring range:	2V, 20V, 200V, 600V
AC voltage measuring accuracy:	±(1% + 3 digit)
Resistance measuring range:	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ
Diode test:	1mA @1.5V
Continuity test:	acoustic indication, <70Ω
Dimensions:	130x52x24mm
Weight with battery:	135g
Power supply:	battery R03 AAA 1,5V x3
Measurement:	AC current, AC voltage, DC voltage, resistance
Conform to the norm:	CAT III 600V, EN 61010
Protection:	anti-overload OPP
Standard equipment:	test leads
Battery/ rechargeable battery:	battery R03 AAA 1,5V x3
Resistance measuring accuracy:	±(1%+2 digit)

Additional information

Gross weight:	0.226 kg